



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IEEE-841™ Petrochem Motors - NEMA Premium® Efficiency

Frame : 445/7TS
 Output : 200 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3570 rpm
 Slip : 0.83 %
 Voltage : 575 V
 Rated current : 175 A
 Locked rotor current : 1140 A
 Locked rotor current (I_L/I_n) : 6.5
 No-load current : 36.0 A
 Full load torque : 290 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 230 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 14 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1914 lb
 Moment of inertia : 44.677 sq.ft.lb
 Noise level : 81 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.90	95.4
Regreasing interval	4000 h	4000 h	75%	0.89	95.4
Grease amount	27 g	27 g	50%	0.86	95.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #20036ST3HIE447TS-W22

Performed by

Checked