



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IE2 IEC Tru-Metric - TEFC (IP55) Cast Iron Frame

Frame : 315L
 Output : 300 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 460 V
 Rated current : 349 A
 Locked rotor current : 2720 A
 Locked rotor current (I_L/I_n) : 7.8
 No-load current : 150 A
 Full load torque : 1306 lb.ft
 Locked rotor torque : 280 %
 Breakdown torque : 250 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 14 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 3574 lb
 Moment of inertia : 327.96 sq.ft.lb
 Noise level : 71 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6319 C3	6316 C3	100%	0.83	95.4
Regreasing interval	13000 h	16000 h	75%	0.78	95.4
Grease amount	45 g	34 g	50%	0.65	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #22012EP3Y315L-W22

Performed by

Checked