



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 Crusher Duty TEFC (IP55)

Frame : 586/7Z
 Output : 250 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 460 V
 Rated current : 304 A
 Locked rotor current : 1820 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 125 A
 Full load torque : 1088 lb.ft
 Locked rotor torque : 190 %
 Breakdown torque : 220 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 12 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 3263 lb
 Moment of inertia : 226.18 sq.ft.lb
 Noise level : 77 dB(A)

	D.E.	N.D.E.
Bearings	NU-324 C3	6319 C3
Regreasing interval	6000 h	13000 h
Grease amount	72 g	45 g

Load	Power factor	Efficiency (%)
100%	0.80	95.4
75%	0.76	95.4
50%	0.66	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #25012EP3GKD580Z-W22

Performed by

Checked