



# Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase : Explosion Proof - High Efficiency

Frame : 586/7T  
 Output : 250 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1190 rpm  
 Slip : 0.83 %  
 Voltage : 460 V  
 Rated current : 305 A  
 Locked rotor current : 1830 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.0  
 No-load current : 106 A  
 Full load torque : 1088 lb.ft  
 Locked rotor torque : 180 %  
 Breakdown torque : 210 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 74 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP54  
 Approximate weight : 3916 lb  
 Moment of inertia : 226.18 sq.ft.lb  
 Noise level : 77 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	9212 h	11094 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.80	95.0
75%	0.76	94.1
50%	0.68	93.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #25012XP3G586/7

Performed by

Checked