



# Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase: W22 IE2 IEC Tru-Metric - TEFC (IP55) Cast Iron Frame

Frame : 355M/L  
 Output : 350 HP  
 Frequency : 60 Hz  
 Poles : 4  
 Full load speed : 1790 rpm  
 Slip : 0.56 %  
 Voltage : 460 V  
 Rated current : 401 A  
 Locked rotor current : 3130 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.8  
 No-load current : 138 A  
 Full load torque : 1013 lb.ft  
 Locked rotor torque : 240 %  
 Breakdown torque : 270 %  
 Design : ---  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 18 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 3241 lb  
 Moment of inertia : 183.38 sq.ft.lb  
 Noise level : 81 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	6000 h	8000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.85	95.8
75%	0.81	95.4
50%	0.70	95.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #26018EP3Y355M/L-W22

Performed by

Checked