



# Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W22 High Efficiency

Frame : 447/9T  
Output : 300 HP  
Frequency : 60 Hz  
Poles : 6  
Full load speed : 1185 rpm  
Slip : 1.25 %  
Voltage : 460 V  
Rated current : 350 A  
Locked rotor current : 2420 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.9  
No-load current : 135 A  
Full load torque : 1312 lb.ft  
Locked rotor torque : 240 %  
Breakdown torque : 240 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 10 s (hot)  
Service factor : 1.15  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 2613 lb  
Moment of inertia : 169.07 sq.ft.lb  
Noise level : 70 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	11000 h	13000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.83	95.0
75%	0.79	95.4
50%	0.69	95.0

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #30012EP3G449T-W22

Performed by

Checked