



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : W22 NEMA Premium - Ball Bearings

Frame : 586/7T
 Output : 300 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 460 V
 Rated current : 356 A
 Locked rotor current : 2140 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 156 A
 Full load torque : 1306 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 200 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 30 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 3495 lb
 Moment of inertia : 277.07 sq.ft.lb
 Noise level : 77 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	11000 h	13000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.81	95.8
75%	0.78	95.8
50%	0.69	95.4

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #30012ET3G586/7-W22

Performed by

Checked