



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 449T
 Output : 300 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 460 V
 Rated current : 351 A
 Locked rotor current : 2770 A
 Locked rotor current (I_L/I_n) : 7.9
 No-load current : 152 A
 Full load torque : 1306 lb.ft
 Locked rotor torque : 280 %
 Breakdown torque : 300 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 7 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 3197 lb
 Moment of inertia : 144.52 sq.ft.lb
 Noise level : 70 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6322 C3	6319 C3	100%	0.82	95.8
Regreasing interval	9212 h	11094 h	75%	0.77	95.4
Grease amount	60 g	45 g	50%	0.66	95.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #30012XT3G449T

Performed by

Checked