



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 586/7T
 Output : 350 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 895 rpm
 Slip : 0.56 %
 Voltage : 460 V
 Rated current : 424 A
 Locked rotor current : 2710 A
 Locked rotor current (I_L/I_n) : 6.4
 No-load current : 260 A
 Full load torque : 2026 lb.ft
 Locked rotor torque : 150 %
 Breakdown torque : 220 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 22 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 4311 lb
 Moment of inertia : 484.35 sq.ft.lb
 Noise level : 75 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	14000 h	17000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.81	95.0
75%	0.77	95.4
50%	0.66	94.8

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #35009EP3G586/7-W22

Performed by

Checked