



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 Crusher Duty TEFC (IP55)

Frame : 586/7
 Output : 350 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 895 rpm
 Slip : 0.56 %
 Voltage : 460 V
 Rated current : 429 A
 Locked rotor current : 2870 A
 Locked rotor current (I_L/I_n) : 6.7
 No-load current : 190 A
 Full load torque : 2026 lb.ft
 Locked rotor torque : 160 %
 Breakdown torque : 230 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 34 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 4309 lb
 Moment of inertia : 484.35 sq.ft.lb
 Noise level : 75 dB(A)

	D.E.	N.D.E.
Bearings	NU-322 C3	6319 C3
Regreasing interval	13000 h	17000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.80	95.0
75%	0.75	95.4
50%	0.64	95.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #35009EP3GKD586/7-W22

Performed by

Checked