



# Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W22 NEMA Premium - Ball Bearings

Frame : 586/7T  
Output : 350 HP  
Frequency : 60 Hz  
Poles : 8  
Full load speed : 895 rpm  
Slip : 0.56 %  
Voltage : 460 V  
Rated current : 426 A  
Locked rotor current : 2730 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.4  
No-load current : 190 A  
Full load torque : 2026 lb.ft  
Locked rotor torque : 160 %  
Breakdown torque : 230 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 34 s (hot)  
Service factor : 1.00  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 4309 lb  
Moment of inertia : 484.35 sq.ft.lb  
Noise level : 75 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	14000 h	17000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.80	95.8
75%	0.75	95.8
50%	0.64	95.4

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #35009ET3G586/7-W22

Performed by

Checked