



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 586/7T
Output : 350 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1190 rpm
Slip : 0.83 %
Voltage : 460 V
Rated current : 422 A
Locked rotor current : 2570 A
Locked rotor current (I_L/I_n) : 6.1
No-load current : 170 A
Full load torque : 1524 lb.ft
Locked rotor torque : 180 %
Breakdown torque : 210 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 29 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 3784 lb
Moment of inertia : 327.96 sq.ft.lb
Noise level : 77 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	11000 h	13000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.81	95.4
75%	0.77	95.4
50%	0.66	95.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #35012EP3G586/7-W22

Performed by

Checked