



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - High Efficiency

Frame : 586/7T
 Output : 350 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 460 V
 Rated current : 428 A
 Locked rotor current : 2650 A
 Locked rotor current (I_L/I_n) : 6.2
 No-load current : 144 A
 Full load torque : 1524 lb.ft
 Locked rotor torque : 180 %
 Breakdown torque : 200 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 73 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP54
 Approximate weight : 4520 lb
 Moment of inertia : 327.96 sq.ft.lb
 Noise level : 77 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	9212 h	11094 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.80	95.4
75%	0.77	94.1
50%	0.70	93.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #35012XP3G586/7

Performed by

Checked