



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : W22 NEMA Premium - Ball Bearings

Frame : 588/9T
 Output : 400 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 895 rpm
 Slip : 0.56 %
 Voltage : 460 V
 Rated current : 498 A
 Locked rotor current : 3340 A
 Locked rotor current (I_L/I_n) : 6.7
 No-load current : 240 A
 Full load torque : 2315 lb.ft
 Locked rotor torque : 150 %
 Breakdown torque : 240 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 25 s (hot)
 Service factor : 1.00
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 4851 lb
 Moment of inertia : 536.85 sq.ft.lb
 Noise level : 75 dB(A)

	D.E.	N.D.E.
Bearings	6322 C3	6319 C3
Regreasing interval	14000 h	17000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.79	95.7
75%	0.73	95.6
50%	0.62	95.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #40009ET3G588/9-W22

Performed by

Checked