



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 NEMA Premium - Roller Bearings

Frame : L447/9T
Output : 400 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1190 rpm
Slip : 0.83 %
Voltage : 460 V
Rated current : 477 A
Locked rotor current : 3290 A
Locked rotor current (I_L/I_n) : 6.9
No-load current : 200 A
Full load torque : 1741 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 250 %
Design : A
Insulation class : F
Temperature rise : 105 K
Locked rotor time : 13 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 3682 lb
Moment of inertia : 278.34 sq.ft.lb
Noise level : 71 dB(A)

	D.E.	N.D.E.
Bearings	NU-322 C3	6319 C3
Regreasing interval	7000 h	13000 h
Grease amount	60 g	45 g

Load	Power factor	Efficiency (%)
100%	0.82	95.8
75%	0.78	95.8
50%	0.68	95.4

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #40012ET3GRB449T-W22

Performed by

Checked