



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : W22 NEMA Premium - Ball Bearings

Frame : 588/9TS
 Output : 600 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3585 rpm
 Slip : 0.42 %
 Voltage : 460 V
 Rated current : 650 A
 Locked rotor current : 4810 A
 Locked rotor current (I_L/I_n) : 7.4
 No-load current : 155 A
 Full load torque : 867 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 270 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 33 s (hot)
 Service factor : 1.00
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 4410 lb
 Moment of inertia : 155.23 sq.ft.lb
 Noise level : 89 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	4000 h	4000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.90	96.5
75%	0.89	96.5
50%	0.84	96.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #60036ET3G588/9S-W22

Performed by

Checked