



Dealers Industrial Equipment

No.:

Date: 29-SEP-2016

DATA SHEET

Single-phase induction motor - Squirrel cage rotor

Customer :
Product line : Pool & Spa Motors : Square Flange - Start Capacitor - High Service Factor

Frame : K48Y
Output : 0.75 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3510 rpm
Slip : 2.50 %
Voltage : 115/230 V
Rated current : 11.2/5.60 A
Locked rotor current : 70.6/35.3 A
Locked rotor current (I_L/I_n) : 6.3
No-load current : 8.30/4.15 A
Full load torque : 1.11 lb.ft
Locked rotor torque : 190 %
Breakdown torque : 340 %
Design : ---
Insulation class : B
Temperature rise : 80 K
Locked rotor time : 6 s (hot)
Service factor : 1.65
Duty cycle : S1
Ambient temperature : -20°C - +50°C
Altitude : 1000 m
Degree of Protection : IP21
Approximate weight : 27 lb
Moment of inertia : 0.02966 sq.ft.lb
Noise level : ---

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6203 2RS	6203 ZZ	100%	0.66	65.8
Regreasing interval	---	---	75%	0.58	63.0
Grease amount	---	---	50%	0.48	54.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #PCQ107H

Performed by

Checked