


Notes: Downloaded from <http://dealerselectric.com>  
Generated for Model #.3336OT3E56C-S

|       |                |        |        |        |
|-------|----------------|--------|--------|--------|
| P     | AB             | J      | 2E     | A      |
| 6.456 | 3.323          | 1.732  | 4.874  | 6.535  |
| H     | G              | HB     | HK     | T      |
| 0.343 | 0.120          | 1.784  | 2.629  | 0.004  |
| O     | FC             | 2F     | B      | C      |
| 6.724 | 6.299          | 3.000  | 4.016  | 10.315 |
| BA    | N-W            | ES     | d1     | S      |
| 2.750 | 1.874          | 1.417  | A 3.15 | 0.187  |
| U     | AA             | depth  | R      | LL     |
| 0.625 | NPT 1/2"       | 0.187  | 0.517  | 4.563  |
| LM    | D              | Flange | AJ     | AK     |
| 4.090 | 3.500          | FC-149 | 5.874  | 4.500  |
| BD    | BF             | BB     | AH     |        |
| 6.450 | UNC 3/8"x16-2B | 0.157  | 2.062  |        |

|               |   |             |   |
|---------------|---|-------------|---|
| Performed by: | Three Phase: W01 (Rolled Steel) - ODP - Premium Efficiency (DOE)<br><br>Three-phase induction motor<br>Frame 56 - ODP | 12-SEP-2016 |  |
| Checked:      |   |             |   |
| Customer:     |   |             |   |
|               |   |             |   |