



Notes: Downloaded from <http://dealerselectric.com>  
 Generated for Model #00156ES1E143JM

|             |             |                   |                  |                    |
|-------------|-------------|-------------------|------------------|--------------------|
| 2E<br>5.500 | 2F<br>4.000 | H<br>0.344        | BA<br>2.560      | A<br>6.457         |
| B<br>5.157  | D<br>3.500  | G<br>0.547        | J<br>1.496       | K<br>1.654         |
| O<br>7.000  | P<br>7.047  | AB<br>6.968       | AA<br>NPT 3/4"   | ER<br>4.258        |
| EQ<br>0.630 | ET<br>2.880 | U<br>0.874        | EM<br>1.000      | EL<br>1.156        |
| EP<br>1.179 | S<br>0.187  | R<br>0.768        | ES<br>1.654      | d1<br>EUNC 3/8"-16 |
| t1<br>0.748 | t2<br>1.102 | C<br>15.866       | Flange<br>FC-149 | AJ<br>5.874        |
| AK<br>4.500 | BD<br>6.496 | BF<br>UNC 3/8"x16 | BB<br>0.157      | AH<br>4.258        |

Performed by:

Checked:

Customer:

Close Coupled Pump : Single-Phase - "JM" Type - TEFC - Standard Efficiency

Single-phase induction motor  
 Frame 143JM - IP55

12-SEP-2016

