



Notes: Downloaded from <http://dealerselectric.com>
Generated for Model #00158OS3E56C-S

| | | | | |
|-------|----------------|-------------|--------|--------|
| P | AB | J | 2E | A |
| 6.456 | 5.882 | 1.732 | 4.874 | 6.535 |
| H | G | HB | HK | T |
| 0.343 | 0.120 | 1.783 | 2.638 | 0.004 |
| O | FC | 2F | B | C |
| 6.724 | 7.480 | 3.000/5.000 | 6.496 | 11.496 |
| BA | N-W | ES | d1 | S |
| 2.750 | 1.874 | 1.417 | A 3.15 | 0.187 |
| U | AA | depth | R | LL |
| 0.625 | NPT 1/2" | 0.187 | 0.517 | 4.543 |
| LM | D | Flange | AJ | AK |
| 4.106 | 3.500 | FC-149 | 5.874 | 4.500 |
| BD | BF | BB | AH | |
| 6.450 | UNC 3/8"x16-2B | 0.157 | 2.062 | |

| | |
|---|-------------|
| Performed by: | |
| Checked: | |
| Customer: | |
| Three Phase: W01 (Rolled Steel) - ODP - Standard Efficiency | |
| Three-phase induction motor Frame 56H - ODP | 12-SEP-2016 |

