



Notes: Downloaded from <http://dealerselectric.com>
 Generated for Model #00536EP3E184JP-W22

| | | | | |
|-------------|-------------|--------|--------|--------------|
| 2E | J | A | P | AB |
| 7.500 | 1.614 | 8.661 | 8.740 | 7.565 |
| 2F | B | BA | D | G |
| 4.500/5.500 | 6.969 | 2.750 | 4.500 | 0.394 |
| O | T | H | AA | EQ |
| 9.343 | 1.772 | 0.406 | NPT 1" | 1.563 |
| ET | U | EM | EL | EP |
| 5.941 | 0.874 | 1.000 | 1.250 | 1.376 |
| ES | t1 | t2 | C | d1 |
| 1.575 | 0.748 | 1.102 | 20.475 | EUNC 3/8"-16 |
| HH | HK | HB | LL | LM |
| 5.500 | 3.150 | 2.236 | 5.512 | 5.236 |
| S | R | Flange | AJ | AK |
| 0.187 | 0.768 | FC-149 | 5.874 | 4.500 |
| BD | BF | BB | AH | |
| 6.496 | UNC 3/8"x16 | 0.157 | 7.319 | |

Performed by:

Checked:

Customer:

Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - High Efficiency

Three-phase induction motor
 Frame 182/4JP - IP55

13-SEP-2016

