



Notes: Downloaded from <http://dealerselectric.com>
Generated for Model #02018OP3E256JM

| | | | | |
|--------------|--------|--------|-------------|------------|
| 2E | A | 2F | B | J |
| 10.000 | 12.130 | 10.000 | 11.732 | 2.520 |
| BA | D | K | G | O |
| 4.500 | 6.220 | 2.560 | 0.787 | 12.204 |
| P | T | AB | H | AA |
| 11.812 | 2.165 | 10.079 | 0.531 | NPT 1 1/2" |
| ER | EQ | ET | U | EM |
| 5.250 | 0.630 | 3.006 | 1.249 | 1.375 |
| EL | S | EP | R | ES |
| 1.750 | 0.250 | 1.750 | 1.110 | 2.559 |
| d1 | t1 | t2 | C | Flange |
| EUNC 1/2"-13 | 0.984 | 1.496 | 23.902 | FC-184 |
| AJ | AK | BD | BF | BB |
| 7.250 | 8.500 | 8.858 | UNC 1/2"x13 | 0.250 |
| AH | | | | |
| 5.250 | | | | |

Performed by:

Checked:

Customer:

Close Coupled Pump : Three-Phase - "JM" Type - ODP - High Efficiency

Three-phase induction motor
Frame 256JM - IP23

23-SEP-2016

