



Notes: Downloaded from <http://dealerselectric.com>
 Generated for Model #02036EP3H256JP-W22

| | | | | |
|--------------|--------|-------------|--------|------------|
| 2E | J | A | P | AB |
| 10.000 | 2.539 | 12.126 | 12.953 | 10.483 |
| 2F | K | B | BA | D |
| 8.252/10.000 | 2.559 | 11.732 | 4.250 | 6.250 |
| G | O | T | H | AA |
| 0.827 | 12.598 | 2.087 | 0.531 | NPT 1 1/2" |
| EQ | ET | U | EM | EL |
| 2.382 | 5.886 | 1.249 | 1.375 | 1.750 |
| EP | ES | t1 | t2 | C |
| 1.770 | 2.480 | 0.984 | 1.496 | 29.106 |
| d1 | HH | HK | HB | LL |
| EUNC 1/2"-13 | 9.250 | 3.976 | 3.061 | 7.815 |
| LM | S | R | Flange | AJ |
| 7.480 | 0.250 | 1.110 | FC-184 | 7.252 |
| AK | BD | BF | BB | AH |
| 8.500 | 8.858 | UNC 1/2"x13 | 0.248 | 8.130 |

Performed by:

Checked:

Customer:

Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - High Efficiency

Three-phase induction motor
 Frame 254/6JP - IP55

23-SEP-2016

