

1 2 3 4 5 6 7 8

A

B

C

D

E

F



Notes: Downloaded from <http://dealerselectric.com>
Generated for Model #02536EP3E256JP-S

| | | | | |
|--------------------|-------------------|------------------|--------------|-------------|
| 2E 10.000 | J 1.693 | A 11.417 | P 13.180 | AB 9.448 |
| 2F 8.252/10.000 | B 11.417 | BA 4.750 | D 6.250 | G 0.187 |
| O 12.010 | T 0.830 | H 0.530 | AA 1.732" | ER 8.130 |
| EQ 2.382 | ET 5.886 | U 1.249 | EM 1.375 | EL 1.750 |
| EP 1.769 | ES 2.559 | t1 1.024 | t2 1.496 | C 27.717 |
| CH 1.929 | FC 13.780 | Flange FC-184 | AJ 7.250 | AK 8.500 |
| BD 11.084 | BF UNC 1/2"x13 | BB 0.250 | AH 8.130 | |

| | |
|--|-------------|
| Performed by: | |
| Checked: | |
| Customer: | |
| Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JP" Type - TEFC - High | |
| Three-phase induction motor Frame 254/6JP - IP55 | 23-SEP-2016 |

