



| | | | | |
|--------------|--------|-------------|--------|------------|
| 2E | J | A | P | AB |
| 11.000 | 3.071 | 13.780 | 14.173 | 11.073 |
| 2F | K | B | BA | D |
| 9.500/11.000 | 3.583 | 13.071 | 4.750 | 7.000 |
| G | O | T | H | AA |
| 1.023 | 14.067 | 2.087 | 0.531 | NPT 1 1/2" |
| EQ | ET | U | EM | EL |
| 2.382 | 5.886 | 1.249 | 1.375 | 1.750 |
| EP | ES | t1 | t2 | C |
| 2.163 | 2.480 | 0.984 | 1.102 | 31.575 |
| d1 | HH | HK | HB | LL |
| EUNC 1/2"-13 | 10.250 | 3.976 | 3.535 | 7.815 |
| LM | S | R | Flange | AJ |
| 7.480 | 0.250 | 1.110 | FC-279 | 11.000 |
| AK | BD | BF | BB | AH |
| 12.500 | 13.593 | UNC 5/8"x11 | 0.248 | 8.130 |

Notes: Downloaded from <http://dealerselectric.com>
 Generated for Model #02536ET3H284JP-W22

Performed by:

Checked:

Customer:

Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - NEMA Premium

Three-phase induction motor
 Frame 284/6JP - IP55

23-SEP-2016

