



## Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

Customer :

### TECHNICAL PROPOSAL

## Three-phase induction motor - Squirrel cage rotor

Product line : W22 Cooling Tower Motors: NEMA Premium - TEFC

Catalog Number : 01518ET3ECT254TF1-W2

List Price : \$2,122

#### Notes:

Downloaded from <http://dealerselectric.com>

Generated for Model #01518ET3ECT254TF1-W2

Performed by:

Checked:



## Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

### DATA SHEET

#### Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : W22 Cooling Tower Motors: NEMA Premium - TEFC

Frame : 254T  
Output : 15 HP  
Frequency : 60 Hz  
Poles : 4  
Full load speed : 1765 rpm  
Slip : 1.94 %  
Voltage : 208-230/460 V  
Rated current : 39.8-36.0/18.0 A  
Locked rotor current : 230/115 A  
Locked rotor current (I<sub>L</sub>/I<sub>N</sub>) : 6.4  
No-load current : 16.0/8.00 A  
Full load torque : 44.0 lb.ft  
Locked rotor torque : 230 %  
Breakdown torque : 270 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 17 s (hot)  
Service factor : 1.25  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 251 lb  
Moment of inertia : 2.6198 sq.ft.lb  
Noise level : 64 dB(A)

|                     | D.E.        | N.D.E.      |
|---------------------|-------------|-------------|
| Bearings            | 6309 2RS-C3 | 6209 2RS-C3 |
| Regreasing interval | ---         | ---         |
| Grease amount       | ---         | ---         |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.83         | 92.4           |
| 75%  | 0.78         | 91.7           |
| 50%  | 0.68         | 91.0           |

#### Notes:

Downloaded from <http://dealerselectric.com>

Generated for Model #01518ET3ECT254TF1-W2

Performed by

Checked




## Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

### PERFORMANCE CURVES RELATED TO RATED OUTPUT

Three-phase induction motor - Squirrel cage rotor



Customer :  
Product line : W22 Cooling Tower Motors: NEMA Premium - TEFC

|                  |                    |                                                        |         |
|------------------|--------------------|--------------------------------------------------------|---------|
| Frame            | : 254T             | Locked rotor current (I <sub>L</sub> /I <sub>n</sub> ) | : 6.4   |
| Output           | : 15 HP            | Duty cycle                                             | : S1    |
| Frequency        | : 60 Hz            | Service factor                                         | : 1.25  |
| Full load speed  | : 1765 rpm         | Design                                                 | : B     |
| Voltage          | : 208-230/460 V    | Locked rotor torque                                    | : 230 % |
| Rated current    | : 39.8-36.0/18.0 A | Breakdown torque                                       | : 270 % |
| Insulation class | : F                |                                                        |         |

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #01518ET3ECT254TF1-W2

Performed by

Checked




## Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

### CHARACTERISTIC CURVES RELATED TO SPEED

Three-phase induction motor - Squirrel cage rotor



Customer :  
Product line : W22 Cooling Tower Motors: NEMA Premium - TEFC

|                  |                    |                                                        |         |
|------------------|--------------------|--------------------------------------------------------|---------|
| Frame            | : 254T             | Locked rotor current (I <sub>L</sub> /I <sub>n</sub> ) | : 6.4   |
| Output           | : 15 HP            | Duty cycle                                             | : S1    |
| Frequency        | : 60 Hz            | Service factor                                         | : 1.25  |
| Full load speed  | : 1765 rpm         | Design                                                 | : B     |
| Voltage          | : 208-230/460 V    | Locked rotor torque                                    | : 230 % |
| Rated current    | : 39.8-36.0/18.0 A | Breakdown torque                                       | : 270 % |
| Insulation class | : F                |                                                        |         |

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #01518ET3ECT254TF1-W2

Performed by

Checked

1 2 3 4 5 6 7 8

A




B

C

D

E

F



Notes: Downloaded from <http://dealerselectric.com>  
Generated for Model #01518ET3ECT254TF1-W2

Performed by:

Checked:

Customer:

W22 Cooling Tower Motors: NEMA Premium - TEFC

Three-phase induction motor  
Frame 254T - IP55

23-SEP-2016



|              |             |                  |             |                |
|--------------|-------------|------------------|-------------|----------------|
| 2E<br>10.000 | J<br>2.539  | A<br>12.126      | P<br>12.480 | AB<br>10.483   |
| 2F<br>8.252  | K<br>2.559  | B<br>10.000      | BA<br>4.250 | U<br>1.625     |
| N-W<br>4.000 | ES<br>2.756 | S<br>0.375       | R<br>1.416  | depth<br>0.375 |
| D<br>6.250   | G<br>0.827  | HB<br>3.061      | O<br>12.598 | T<br>2.087     |
| HF<br>6.565  | HH<br>8.376 | HK<br>3.976      | H<br>0.531  | C<br>23.213    |
| LL<br>7.815  | LM<br>7.480 | AA<br>NPT 1 1/2" | d1<br>A 4   | d2<br>A 4      |

